
RENAISSANCE

TILE
&
BATH

SPECIFICATIONS

Porcelain

APPLICATIONS:

All porcelain collections are recommended for interior use. Exterior use, use manufacturer's specifications. This material is suited for vertical and horizontal applications such as backsplashes, walls, floors, shower walls, shower floors, etc.

PROPERTIES:

All porcelain tiles are subject to variation in shade and size.

INSTALLATION

It is important to select a qualified installer with experience installing the materials specified. All materials should be inspected and approved before installation. Installation constitutes acceptance of the product. For specific installation instructions, consult the *Handbook for Ceramic Tile Installation* from the Tile Council of North America, Inc.

To ensure satisfactory results, it is recommended that all materials be blended and laid out prior to installation.

CARE AND MAINTENANCE

Most general cleaning can be done with a non-abrasive cloth and a pH-balanced cleaner. Cleaning products containing chlorine and ammonia should be avoided, as they could etch the surface of the tile. For additional general cleaning questions, contact a Renaissance Tile & Bath design consultant for further information.

RENAISSANCE

TILE
&
BATH

Model

LAUD 5.4"X5.4" COLLECTION

Manufacture process

Porcelain white body, double firing

Nominal size (mm)

136X136X9

Group

BIla

TEST	RESULT	TESTING STANDARD
Water absorption	0,5%<E≤10%	UNE-EN ISO 10545-3
Breaking strength N/mm ²	E>22 N/mm ²	UNE-EN ISO 10545-4
Thermal shock resistance	Resist	UNE-EN ISO 10545-9
Crazing resistance	Resist	UNE-EN ISO 10545-11
Chemical resistance	Type A	UNE-EN ISO 10545-13
Resistance to stains	Class 4	UNE-EN ISO 10545-14
Tone Variation	Lightweight V2	

APPLICATIONS AND SAFETY INFORMATION

Ceramic product suitable for wall and floor applications, both indoors and outdoors, according to the conditions of use and installation

A minimum joint width of 2 mm is recommended, using a grout suitable for ceramic tiles and compatible with the conditions of use

Use a C2 cementitious adhesive, in accordance with UNE-EN 12004, suitable for the substrate, tile format and conditions of use

RENAISSANCE

TILE
&
BATH

Model

LAUD 2.5"X10" COLLECTION

Manufacture process

Porcelain white body, double firing

Nominal size (mm)

63x250x9

Group

Blla

TEST	RESULT	TESTING STANDARD
Water absorption	0,5%<E≤10%	UNE-EN ISO 10545-3
Breaking strength N/mm ²	E>22 N/mm ²	UNE-EN ISO 10545-4
Thermal shock resistance	Resist	UNE-EN ISO 10545-9
Crazing resistance	Resist	UNE-EN ISO 10545-11
Chemical resistance	Type A	UNE-EN ISO 10545-13
Resistance to stains	Class 4	UNE-EN ISO 10545-14
Tone Variation	Lightweight V2	

APPLICATIONS AND SAFETY INFORMATION

Ceramic product suitable for wall and floor applications, both indoors and outdoors, according to the conditions of use and installation

A minimum joint width of 2 mm is recommended, using a grout suitable for ceramic tiles and compatible with the conditions of use